

FLASHING ARROW SIGN

'B' SIZE

ATS Flashing Arrow Sign – Type B complies with specifications AS/NZS4192: 2006 and RTA FAS/5.

The sign is designed for roof mounting on vehicles. It is fully self-contained to provide advance and directional traffic information whilst minimising power consumption.

ATS Arrow Signs are constructed with aluminium frames and panels and are powder coated to give a lightweight durable piece of equipment.



FEATURES

- » Microprocessor controlled
- » Low voltage protection with automatic switch to warning mode for overload protection
- » Built-in lamp failure detection
- » Fail-safe operation of the sign under fault conditions
- » Four operational modes: Arrow Right, Double Headed Arrow, Arrow Left, Warning
- » LED controller display for operation status
- » Automatic dimming facility in conjunction with an in-built light sensor
- » Luminous intensity levels and colour as per AS/NZS 4192:2006 specification
- » 50,000 hour ultra bright LEDs
- » Operates reliably under all weather conditions
- » LED Rotator Beacon with white LED's with amber cover. Multi-function strobe/flash with rotator effect.

SPECIFICATIONS

MODEL	TYPE B
Size	770 x 1500
Panel Weight	24 kg
No. Lamps Face	15
Maximum Current	8 amps
Flash Cycles	35-40 per minute
Visibility Distance	860 metres

CATALOGUE NO. DESCRIPTION

ABV-RA7001	Arrowboard B Vehicle Mount STD
ABV-RA7001C	Arrowboard B Vehicle Mount AS Compliant
ABV-RA7001-R	Arrowboard B Vehicle Mount STD Rotator Option
ABV-RA7001C-R	Arrowboard B Vehicle Mount AS Compliant Rotator Option
ERB-A-12V	Emergency Rotating Beacon Amber 12v LED
ERB-C-12V	Emergency Rotating Beacon Clear 12v LED

